

# $B \rightarrow K\ell\ell$ update



Marcin Chrzęszcz  
Gośka Pikies



University of  
Zurich <sup>UZH</sup>

$R(K)$  meeting, CERN  
March 01, 2016

# Feature engineering

$\Rightarrow$  We wanted to align the training with  $B \rightarrow K_{ee}$ .  
The base is:


- K\_Kst\_IPCHI2\_OWNPV
- B\_plus\_ENDVERTEX\_CHI2
- e\_minus\_IPCHI2\_OWNPV
- e\_plus\_IPCHI2\_OWNPV
- B\_plus\_PT
- B\_plus\_IPCHI2\_OWNPV
- B\_plus\_FD\_OWNPV
- B\_plus\_DIRA\_OWNPV
- B\_plus\_P
- K\_Kst\_P
- e\_plus\_TRACK\_CHI2NDOF
- e\_minus\_TRACK\_CHI2NDOF
- K\_Kst\_TRACK\_CHI2NDOF

$\Rightarrow$  In addition we have extensions:

- K\_Kst\_MC12TuneV2\_ProbNNk (kpid)
- K\_Kst\_PT (kpt, ep)
- e\_plus\_PT (ep)
- e\_minus\_PT (ep)







# Performance

⇒ The performance of the training (10-Fold training)







# Put or not to put PIDK in BDT

⇒ Cuts:  $K\_Kst\_MC12TuneV2\_ProbNNk > 0.1, 0.2, 0.3, 0.4, 0.5, 0.6$ .





# Fold consistency

⇒ Comparison of the ROC curves





# Distribution consistency

⇒ Comparison of the Distributions (base):





# Distribution consistency

⇒ Comparison of the Distributions (kpid):





# Distribution consistency

⇒ Comparison of the Distributions (kpt):



# Distribution consistency

⇒ Comparison of the Distributions (ep):



# Conclusions

- Large portion of efficiency gain of `K_Kst_MC12TuneV2_ProbNNk` inside the BDT can be recovered by applying a `K_Kst_MC12TuneV2_ProbNNk` cut.
- I would still go with putting it inside the BDT, as it makes life easier.
- See what other people working in this say.

